



# 45368 ROUND FIXED DOWNLIGHT



The Midway collection is a family of integrated led recessed lights available in sizes ranging from 2"-6". With their durable die cast aluminum bodies and built on CCT color selecting switch Midway family fixtures are aesthetically appealing, functional and extremely versatile. Their IC rated shallow bodies allow them to be used in most residential and commercial installations with or without insulation in the ceiling. Midway fixtures are available in white or black finish and come standard with a reliable phase dimming power supply.

TYPE:		
DATE:		
NOTES:		



2700K . 3000K . 3500K . 4000K . 5000K

# **SPECIFICATIONS**

#### LIGHT HOUSING

- IC Airtight Cast aluminum body.
- Remodel application. C/W spring loaded clips.
- Mates to driver box with quick connector.
- Max Ceiling thickness 5/8".
- Approved for damp location.

#### DIMENSIONS

- Cut hole: ø3 3/4".
- Fixture: ø4 3/8" x 3 1/4"H.

#### **ELECTRICAL**

- 120 V Input class 2 constant current dimmable driver enclosed in junction box.
- TRIAC and ELV dimming.
- Min operating temperature (-4°F~104°F)(-20°C~-40°C).

#### LIGHT MODULE

- 1 x 12W Integrated LED COB.
- Lumen maintenance 70% 50,000 hrs.
- CRI: 90+
- · Beam angle: 38 degree.
- |30K |35K Kelvin (CCT): 27K
- Delivered Lumen: 702 lm |750 lm |818 lm |859 lm |854 lm

#### **CERTIFICATIONS**













40K

### **ORDERING GUIDE**

MODEL	FINISH
45368-028	Black
45368-011	White

#### BEAM WATTS LUMENS KELVIN DIMMABLE CRI **ADJUSTABLE** ANGLE ø3 3/4' TRIAC/ELV 38° N0 12W Up to 859 **CCT Selectable** 90+










PRODUCT DIMENSIONS



## **ACCESSORIES**



45611-018 60" 2 pin Connector



**NEW CONSTRUCTION PLATE** Mounting kit includes bars 14" x 7 3/4" ø3 3/4"



45517-013 **NEW CONSTRUCTION SMASH PLATE** 13 1/4" x 6 1/2" ø3 3/4"



NO IC BOX REQUIRED